CONTOUR

PREVIOUSLY (SIDEWINDER)





1615501 • Clear Lens



1615502 • Smoke Lens



1615503 • Amber Lens



1615504 • Dark ESP Lens



1615505 • Bronze Lens



1652107 • Grey Polarised Lens



- **HIGH GLOSS, DARK GUN METAL DUAL MATERIAL FRAME**
- + ♦ PLATINUM COATING (+P)
- **+** RUBBER NOSE PADS FOR SUPERIOR COMFORT AND NON-SLIP FIT
- + HALF FRAME DUAL LENS DESIGN



CONTOUR

PREVIOUSLY (SIDEWINDER)

MODEL	VERSIONS	PRODUCT CODE	LENS MARKING	FRAME MARKING	COATINGS
CONTOUR (PREVIOUSLY SIDEWINDER)	Clear Lens	1615501	Ю	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog /Platinum+P
	Smoke Lens	1615502	13	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog /Platinum⁺ P
	Amber Lens	1615503	Ю	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog /Platinum+P
	ESP Lens	1615504	I1	AS/NZS 1337.1.2010	Anti-fog Inside
	Bronze Lens	1615505	13	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog /Platinum+P
	Grey Polarised Lens	1652107	13	AS/NZS 1337.1.2010	Hard coat

LENS MARKING

- → Platinum is a permanent coating on both sides of the lens gives them a high resistance to scratching (1.4 cd / m²), to the most aggressive chemicals and delays the onset of fogging for 2 minutes, as per the testing requirements of EN166.
- 1. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses.

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (Clear & Amber).
- 1. Range of luminous transmittance 43 -88% (ESP).
- Range of luminous transmittance 8 -18% (Smoke, Bronze & Grey Polarised).

LENSES

- New moulded lenses
- 2mm polycarbonate
- 8 base curve
- Platinum coating on both sides of Clear, Smoke, Amber and Bronze lenses
- Hard coating on the Grey Polarised lens
- Anti-fog coating on inside ESP lens
- 100% UV 385 Clear
- 100% UV 400 Smoke, Amber, ESP, Bronze and Polarised lenses

FRAME MARKING

AS/NZS 1337.1.2010: Tested and approved to. AS/NZS 1337.1.2010 - Medium Impact protection. Resists a 6mm at 45 m/s.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS			
LENSES	PC - 2,2 mm - Curve 8		
FRAME	PC		
TEMPLES	PC + TPR		
STRAP	Applicable		
FOAM	Applicable		
SPARE LENSES	No		

ASIA/PACIFIC HEADQUARTERS:

Bollé Australia Pty Ltd 32-40 Fairchild Street Heatherton VIC 3202 T: 1300 138 098 E: safety@bolle.com.au NEW ZEALAND:

T.: 0800 2655 369 E: bolle@bolle.co.nz

