

BLAST



Optional Mouth Guard



115 g



1669101 • Blue Frame with SBR Foam / Clear Lens / Top Vent Closed



1669201 • Blue Frame with SBR Foam / Clear Lens / Indirect Top / Bottom Vents



1669203 • Blue Frame with SBR Foam / Clear Lens / Mouth Guard / Indirect Top / Bottom Vents

Accessories:

- 1669205 • Clear Lens Only
 - 1669206 • Smoke Lens Only
 - 1650015 • RX Adaptor
 - 1669204 • Mouth Guard
 - 1650014 • Lens Tear Off
- (1 Pack = 10 Sets / 4 per set)

+ EXCEPTIONAL DUST PROTECTION

+ CAN BE WORN OVER SPECTACLES

& DISPOSABLE RESPIRATORS

+ LOW PROFILE, LIGHT WEIGHT PVC FRAME

+ OPTIONAL MOUTH GUARD

+ MEDIUM IMPACT & CHEMICAL

SPLASH APPROVED

bolle
SAFETY

BLAST

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
BLAST	 Blue Frame with SBR Foam /Clear Lens / Top Vent Closed	1669101	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Blue Frame with SBR Foam / Clear Lens / Indirect Top / Bottom Vents	1669201	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog
	 Blue Frame with SBR Foam /Clear Lens / Mouth Guard / Indirect Top / Bottom Vents	1669203	IO	AS/NZS 1337.1.2010	Anti-scratch/Anti-fog

LENS MARKING

- I. The letter 'I' signifies 'Medium Impact' approval.
- O. The letter 'O' marking signifies that the product has been approved for the use both outdoors and indoors and the terminology used by Australian standards is 'outdoor un-tinted'. This marking appears on all clear, amber and contrast lenses

OCULAR LENS CATEGORY:

- O. Range of luminous transmittance 80-100% (clear).

APPLICATIONS

- Chemical splash protection
- Cutting
- Spraying
- Dust protection
- Acid and alkaline handling
- Wood and metal work

MAIN MARKETS

- Petro Chemical
- Construction
- Manufacturing
- Paint
- Automotive
- Labs

LENSES

- 2mm polycarbonate
- 9 base curve
- 'ALS' anti-fog/anti-scratch coating on both sides of lens: Clear
- 100% UV 385 – Clear

CLEANING AND STORAGE

CLEANING : Bollé Safety recommends only using our **CLEAN** Lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: Store between 5 and 40 °, humidity <90%.

CHARACTERISTICS

LENSES	PC - 2,2 mm
FRAME	PVC
STRAP	Yes
FOAM	SBR
SPARE LENSES	Yes

FRAME MARKING

AS/NZS 1337.1.2010 : Tested and approved to AS/NZS 1337.1.2010 for medium impact and chemical splash protection. Resists a 6mm at 45 m/s.

ASIA/PACIFIC HEADQUARTERS :

Bollé Australia Pty Ltd
32-40 Fairchild Street
Heatherton VIC 3202
T: 1300 138 098
E: safety@bolle.com.au

NEW ZEALAND:

Bollé New Zealand Limited
Unit 5, 114 Sawyers Arms Road
Papanui, Christchurch 8052
T: 03 3751400
E: bolle@bolle.co.nz